



Timer 計時器

Application: Food Machinery, Shoe Machinery, High Temperature Furnace, Packing Machinery, Bakery Oven, Coating Machinery...etc.
用途：食品機械、包裝機械、烤箱、高溫爐、塗裝機械、鞋業機械等的廣泛應用。

ORDERING CODE 訂貨編號

型號 Model No. **T 4 8 4 -**



插座選式 SOCKET TYPE:



(H) 50*70mm



(G) 49*39mm



(F) 52*41mm

計時啟動條件 TIMER STARTING CONDITIONS:

手動計時	MANUAL START	0
送電計時	POWER - ON	1
外部觸發計時	EXTERNAL TRIGGER	2

輸出模式 OUTPUT OPERATION MODE:

一限	TIME LIMIT (1C)	N
二限	2 TIME LIMIT (2C)	A
一瞬一限	INSTANTANEOUS + TIME LIMIT	B

插座選式 SOCKET TYPE:

掛鉤式	front w/ hook	H
反接式	rear wiring	G
正接式	front wiring	F

FEATURES

- Can be used as count up and count down timer.
- Wide time range selectable in the following formats: 999 (hour), 999 (min), 999 (sec), 99.5 (h.m.), 99.5 (m.s.)
- External contact start-up can be set as: immediate start-up and standby start-up.
- Accessible time adjustments even during in the operation mode.
- Selectable time-end mode: time hold, time reset and auto-run mode.
- Interchangeable output contact: A contact, B contact, C contact flicker
- Time-start methods: manual start, during power-on, external contacts
- Output operation mode: time limit (1C), 2 time limit (2C), instantaneous+time limit.

特性

- 正數/倒數計時
- 計時模式提供5種時間單位選擇: 999 (時)、999 (分)、999 (秒)、99.5 (時.分)、99.5 (分.秒)
- 外部接點啟動, 可設定立即啟動及待機啟動功能
- 計時過程中可即時增加或減少時間
- 計時結束動作選擇: 停止計時、延遲計時關閉、無限循環
- 輸出接點可切換: A接點、B接點、C接點閃爍
- 計時模式: 手動計時、送電計時、外部接點啟動計時
- 輸出模式: 一限、二限、一瞬一限


SPECIFICATION

Timing accuracy : $\pm 0.05\%$
Function type : Timer
Contact Output : Relay 250V/3A
Input Power : AC 220V 50/60 Hz (AC 110V; AC/DC 24V: OPTIONAL)
Setting Mode : (Hour),(Min),(Sec),(Hour.Min),(Min.Sec)
Ordering Code : T484 (48mm*48mm only)
Ambient Temperature : -10~55°C, below 90% humidity


規格說明

時間精度 : $\pm 0.05\%$
功能種類 : 計時器
接點輸出 : Relay 250V/3A
入力電源 : AC 220V 50/60 Hz (AC 110V; AC/DC 24V: 選配)
設定模式 : (時)、(分)、(秒)、(時.分)、(分.秒)
訂貨型號 : T484 (48mm X 48mm 單一規格)
環境濕度 : 濕度低於90%, 常溫介於零下10度至55度


WIRING DIAGRAM 接線圖




(T484 - 0N / T484 - 1N)



(T484 - 2N)



(T484 - 0A / T484 - 1A)





(T484 - 0B / T484 - 1B)

Legend:

- Power source (AC)
- Timer delay contact (限)
- Instantaneous contact (瞬)
- Contact on (外部接點)

DIMENSION & PANEL CUTOUT 尺寸圖 & 開孔尺寸



* 開孔尺寸 (Panel Cutout) 44.5 x 44.5 (±0.2) 開 (Cut) 44.5 (±0.2) 正方
(單位 Unit:mm)

附注: 1. 外部觸發計時 (2) 啟動條件, 僅能搭配一限 (N) 輸出模式
2. 時間單位標準為 MIN (分)

Note: 1. Timer starting condition: EXTERNAL TRIGGER (2), is suitable ONLY to output operation mode: TIME LIMIT (N)
2. Standard time unit: MIN